

BEFORE STARTING ENGINES

- [] Gear -- CHECK DOWN and GUARDED
- [] Thrust Levers -- IDLE
- BATT Switches -- ON
- [] Parking Brake -- SET
- [] Fuel Quantity -- CHECK
- [] Gross Weight Counter -- SET
- [] Transfer Pumps -- ALL OFF
- [] Boost Pumps -- OFF
- L and R Crossfeeds -- CLOSED
- [] Inverters -- OFF
- [] Avionics Master Switch -- OFF

STARTING ENGINES

- [] Anti Collision Lights -- ON
- [] Seatbelt & No Smoking -- ON
- Bus Tie -- TIED
- [] Bus C & D -- ON
- [] Boost Pumps -- ON
- [] Motor Switches -- ON
- [] #2 Engine Start Button -- HOLD UNTIL 50% N2
- [] #2 N2 52%-65% -- CHECK
- [] #2 Oil Pressure 25-46 PSI -- CHECK
- [] #2 Oil Temp below °127 C -- CHECK
- [] #2 Engine Instruments -- CHECK NORMAL
- []#2 Generator -- ON
- [] Start Engines 3 and 1 -- REPEAT ABOVE 6 STEPS FOR EACH
- [] Bus Tie -- NORMAL
- [] Transfer Pumps -- ALL ON

AFTER START

- [] Inverters 1 and 2 -- ON
- [] Avionics Master Switch -- ON
- Radios -- SET
- [] Slats -- FIRST GREEN
- [] Flight Controls -- CHECK
- [] Yaw Damper -- OFF
- Parking Brake -- RELEASE

<u>TAXI</u>
[] Nav and Taxi lights ON [] Anti-Ice AS REQUIRED [] Brakes CHECK [] Altimeter SET [] Flight Instruments CHECKED [] Engine Instruments CHECK [] Nav Equipment CHECK
BEFORE TAKEOFF
[] Landing Lights ON [] Transponder SET [] Pitots ON [] FATS(flaps,airbrakes,trim,speeds) SET FOR T/O
TAKEOFF
[] Thrust Lever T/O [] Brakes RELEASE [] VR ROTATE
AFTER TAKEOFF
[] Gear UP AFTER POSITIVE RATE OF CLIMB [] Anti-Ice AS REQUIRED [] Yaw Damper ON [] Slats and Flaps CLEAN AT VFR [] Taxi Lights ON [] Climb Thrust SET [] Seatbelt & No Smoking OFF
CLIMB
CAUTION: Maximum thrust lever setting is MCR with full anti-ice on between 15,500 and 30,000 fee [] Landing Lights OFF AT 10,000 FEET [] Altimeters RESET TO 29.92 CROSSING 18,000 FEET
DESCENT
[] Anti-Ice AS REQUIRED See Flight Manual for landing computations. [] Altimeters RESET TO LOCAL CROSSING 18,000 FEET [] Fuel Quantities and Balance CHECK [] Landing Lights ON BELOW 10,000 FEET
<u>APPROACH</u>
[] Avionics and Radios SET [] Slats and Flaps SET [] L and R Crossfeeds CLOSED [] Seatbelt & No Smoking ON

LANDING

[] Gear -- DN (Check for 3 green lights)
[] Slats and Flaps -- SET
[] Brakes -- AS REQUIRED
[] Autopilot -- OFF
[] Yaw Damper -- OFF
[] Landing and Taxi Lights -- ON

AFTER LANDING/CLEARING RUNWAY

[] Anti-Ice -- OFF [] Pitots -- OFF [] Landing Lights -- OFF [] Airbrakes -- RETRACTED [] Slats and Flaps -- CLEAN [] Trims -- NEUTRAL

SHUTDOWN

[] Parking Brake -- SET
[] All Lights -- OFF
[] Thrust Levers -- IDLE
[] Motor Switches -- OFF
[] Boost Pumps -- OFF
[] Avionics Switch -- OFF
[] Inverters -- OFF
[] Transfer Pumps -- OFF
[] All Generator Switches -- OFF

Copyright © 2005 – Yannick Lavigne, Fred Banting, Rob Young et Eric Dantes